



Electrofusion coupler

PN 10			
D _n	L	A	D
315	234	117	4.7/4.0
355	267	133	4.7/4.0
400 (short)	240	115	4.7/4.0
400	300	150	4.7/4.0
450	310	155	4.7/4.0
500 (short)	260	127	4.7/4.0
500	322	161	4.7/4.0
560	334	167	4.7/4.0
630 (short)	332	166	4.7/4.0
630	376	188	4.7/4.0
710 (short)	350	173	4.7/4.0
710	429	207	4.7/4.0
800 (short)	361	176	4.7/4.0
800	455	222	4.7/4.0

PN 16			
D _n	L	A	D
25	80	37	4.7/4.0
32	90	45	4.7/4.0
40	95	46	4.7/4.0
50	113	56	4.7/4.0
63	112	56	4.7/4.0
75	124	62	4.7/4.0
90	139	69	4.7/4.0
110	148	74	4.7/4.0
125	158	79	4.7/4.0
140	168	84	4.7/4.0
160	173	86	4.7/4.0
180	191	94	4.7/4.0
200	192	96	4.7/4.0
225	218	109	4.7/4.0
250	220	110	4.7/4.0
280	215	107	4.7/4.0
315	265	132	4.7/4.0
315 (short)	235	113	4.7/4.0
355	267	133	4.7/4.0
400 (short)	240	113	4.7/4.0
400	300	147	4.7/4.0
450	310	155	4.7/4.0
500 (short)	260	129	4.7/4.0
500	320	161	4.7/4.0
560	274	136	4.7/4.0
630 (short)	333	161	4.7/4.0
630	375	188	4.7/4.0
710	432	209	4.7/4.0
800	456	224	4.7/4.0

PN 20			
D _n	L	A	D
50	111	55	4.7/4.0
63	112	59.5	4.7/4.0
75	124	62	4.7/4.0
90	139	68	4.7/4.0
110	149	74	4.7/4.0
125	169	82	4.7/4.0
160	173	86	4.7/4.0
200	205	102	4.7/4.0
250	233	116	4.7/4.0
315	266	128	4.7/4.0

PN 25			
D _n	L	A	D
100	159	75	4.7/4.0
110	159	77.7	4.7/4.0
125	158	80	4.7/4.0
160	178	88.8	4.7/4.0
200	197	97	4.7/4.0
250	202	98	4.7/4.0
280	237	52	4.7/4.0