



Reducing Cross Tee

Specification	Size (mm)				Thickness		
	Dn	Dn1	L	H	SDR 17	SDR 13.6	SDR 11
+ 90 x 63	90	63	240	75	√		√
+ 110 x 63	110	63	279	68	√		√
+ 110 x 75	110	75	279	75	√		√
+ 110 x 90	110	90	279	82	√		√
+ 160 x 63	160	63	329	67	√		√
+160 x 75	160	75	329	74	√		√
+160 x 90	160	90	329	82	√		√
+160 x 110	160	110	329	85	√		√
+ 200 x 110	200	110	379	85	√		√
+ 200 x 160	200	160	379	85	√		√
+ 225 x 110	225	110	415	86	√		√
+ 225 x 160	225	160	415	86	√		√
+ 225 x 200	225	200	415	91	√		√
+ 250 x 110	250	110	461	96	√		√
+ 250 x 160	250	160	461	96	√		√
+ 250 x 200	250	200	461	98	√		√
+ 315 x 110	315	110	543	91	√		√
+ 315 x 160	315	160	543	91	√		√
+ 315 x 200	315	200	543	96	√		√
+ 315 x 250	315	250	543	110	√		√
+ 355 x 200	355	200	485	120	√		
+ 400 x 110	400	110	351	120	√		
+ 400 x 200	400	200	439	120	√		
+ 450 x 200	450	200	490	120	√		
+ 450 x 315	450	315	605	130	√		
+ 500 x 110	500	110	356	125	√		
+ 500 x 160	500	160	406	125	√		
+ 500 x 200	500	200	445	135	√		
+ 500 x 250	500	250	495	135	√		
+ 500 x 315	500	315	560	136	√		
+ 500 x 400	500	400	644	136	√		
+ 560 x 200	560	200	515	140	√		
+ 560 x 315	560	315	625	140	√		
+ 630 x 200	630	200	530	140	√		
+ 630 x 315	630	315	660	140	√		
+ 710 x 200	710	200	568	167	√		
+ 710 x 315	710	315	681	167	√		
+ 710 x 400	710	400	794	168	√		
+ 710 x 500	710	500	864	168	√		
+ 710 x 630	710	630	993	168	√		
+ 800 x 200	800	200	606	206	√		
+ 800 x 315	800	315	719	319	√		
+ 800 x 400	800	400	802	402	√		
+ 800 x 500	800	500	902	502	√		
+ 800 x 630	800	630	1031	631	√		